

Armadilha 15 LED (flytrap)



The 15 m² free standing or wall mounted insect control unit

With its discreet and attractive design the Armadilha 15 LED is recommended for use in domestic and professional environments.



Armadilha 15 LED

The discreet insect light trap for areas up to 15 m²

With its discreet and attractive design the **Armadilha 15 LED** is recommended for use in domestic and professional environments.

The **Armadilha 15 LED** is designed to be placed as either a free-standing or wall-mounted unit. The **Armadilha 15 LED** uses a powerful ultraviolet lamp which attracts flying insects. On the inside of the unit a glueboard is placed, which the insects are trapped on. This glueboard is placed out of sight providing discreet control of the flying insect pests. **Armadilha 15 LED** is easy to install, easy to service and safe to use. *The unit is designed for indoor use only.*

10 reasons to start using the Armadilha 15 LED:

- In its free-standing or wall mounted position, the unit offers full discretion.
- Unit can be used in a wide variety of applications
- Glue board discreetly placed out of sight and is easy to replace from the top.
- Plastic housing offers durability.
- Effective coverage of areas up to 15 m².
- Easy to service with direct access to lamp and glue board.
- Meets ISO 9001 / RoHS & the CE standard. Unit is HACCP compliant.
- The heat entrapment design ensures that insects fly in faster.
- High powered effective UV-A LED lamp.
- 1 year full guarantee on the mechanical aspects.



Technical specifications

Area coverage	: 15 m ² effective coverage
Light source	: 1 x 6 Watt UV-A LED
Type of lamp	: UV-A LED Lamp RoHS certified
Position	: Free-standing or wall-mounted
Electrical supply	: 110-240V ~ 50-60 Hz
Catch specifications	: Temperature optimised glue board
Power consumption	: 6 Watt
Weight	: 1 Kg
Material	: Plastic housing
Degree of protection	: IP20
Colour	: White housing / Black top
Int. building norm	: acc. IEC 60.335-259 int. std
Guarantee	: 1 year return to base
Lamp life time	: 15,000 hrs
Dimensions (LxDxH)	: Ø140 x 280 mm
CE-approval	: Yes

